

E003: Refrigerators and freezers

PQS code: E003/120

Type of appliance: Icelined refrigerator Manufacturer's reference: VLS 174A AC Manufactured in: Denmark

Vestfrost Solutions Company: Address: A/S Vestfrost

Falkevej 12 DK-6705 Esbjerg Ø

Denmark

Telephone: +45 7914 2555; +45 7914 2248

Email: clc@vestfrostsolutions.com;

bjn@vestfrostsolutions.com

Web address: http://vestfrostsolutions.com/

Specifications

+5°C Hot Climate zone: Min rated ambient temp:

R600a Electric Mains Refrigerant:

115/60Hz;#8;#Electric Mains 220-**Energy source:** 240V 50/60Hz or Electric Mains

115/60Hz optional

+43°C Ext dimensions (HxLxD) Appliance tested at: H950xL550xW650

Performance at: +43°C Electric - compression Fuel and cycle type:

REFRIGERATOR Freeze protection: Grade A **FREEZER**

Vaccine storage capacity: 38 L

(Litres)

Gross volume (Litres): 50.60 L Gross volume: n/a

Holdover time (hours): 57.52 HOURS Waterpack freezing capacity:

Energy consumption, stable 0.504 KWh/24 h

running (kWh/24 hours): Waterpack storage capacity:

Energy consumption, cool **Energy consumption during**

down test (kWh/24 hours): freezing:

	pre-qualified: 27 Apr 2021	Validity until: May, 2024	
Verification report:	Refrigerator 300-KLAB-20- 317	Verification laboratory:	Danish Technological Institute
Quality standard:	- ISO 9001:2008 -	Specification ref.	
Price			
Price year	2021	Incoterms	EXW
Shipping volume:	0.63 m3	Shipping weight:	79 KG
Spare parts (ref, price):	Compressor (TLES7KTK, Comple Thermostat Starting device Thermometer	ete)	
Accessories:	1 x Vaccine storage baskets; 1 x Bottom grating; 1 x 30 day electronic temperature logger; Self-regulating temperature control; Electronic temperature reading; 2 x Keys; Instruction manual in 6 UN languages; Technical manual in 6 UN languages; Plywood packing/crate		
Comments:	Appliance requires only 4 hours electricity per 24 hours at +43°C Equipped with unique QR code, that can be used along Vestfrost Solutions Unit tracker APP, containing various installation/service features. Electric components positioned in corrosion free metal junction box, protecting for water, dust intrusion, and eases service/maintenance. For easy customization to local standard plug, supplied with appliance power in-let + Appliance power plug/cable. model is supplied with internal voltage stabilizer for extended input range, incl. high, low, spike and surge protection in line with E007/VS01-VP.5 For 220-240V/50/60Hz, input voltage regulation range 110-278V/50/60Hz For 100-127V/50/60Hz, input voltage regulation range 82-159V/50/60Hz		

Note: If Current PQS status is 'Suspended' or 'Withdrawn', this product is NOT to be purchased.