



E006 :	Temperature monitoring devices
PQS code:	E006/029
Description:	40 day electronic shipping indicator
Manufacturer's ref:	VaxAlertTM USB
Manufactured in:	China; People's Republic of
Company:	Sensitech Inc.
Address:	A Business Unit of Carrier Corporation, Suite 258X, 800 Cummings Center. Beverly, MA 01915 United States
Telephone:	+1 978 - 927- 7033
Email:	adeleo@carrier.com , mmarks@carrier.com,
Web address:	http://www.sensitech.com

Specifications

Product type:	40 day Electronic shipping indicator	Display medium:	LCD
Mode of operation:	Electronic	Weight	70.9g
Minimum temperature:	-30°C	Main material:	ABS
Maximum temperature:	+55°C	Dimensions:	10.1 x 5.6 x 1.96
MECHANICAL AND ELE	CTRONIC DEVICES ONLY		
Accuracy:	±0.5°C between -5°C and +25°C	C Min logging interval:	pre-set 2 min
Power source:	Non-replaceable battery	Alarm type:	Visual
Battery type:	3.6V Lithium	User interface:	LCD and PC downloadable
Battery shelf life:	24 mths	Programmability:	Factory programmed
Activated life:	12 mths	IP rating:	64
Memory capacity:	16 000 data points		
	advanced indicator enables logi if and when cold chain breaks o	istics staff, receivers and qu occur in the supply chain. Th	excursion history information. This ality assurance personnel to determine e user-friendly liquid crystal display alarm time-stamp record and the
Comments:	advanced indicator enables logi if and when cold chain breaks o (LCD) combines complete alarm maximum or minimum temperat The indicators are factory config vaccine procurement and transp monitor up to three time-temper monitoring requirements beyond Automatic generation of Adobe of alarms: (1) Single event alarm time period, (2) Cumulative time total sum of time. User-friendly accept/reject decision making a	istics staff, receivers and quecur in the supply chain. The n status information with an ture. gured with WHO established port requirements. These contrature alarms, which can be d WHO/UNICEF vaccine show the vaccine shows are triggered if temperature event alarms are triggered three button interface and in nd detailed excursion histor	ality assurance personnel to determine e user-friendly liquid crystal display alarm time-stamp record and the d alarm profiles in support of UNICEF ist-effective, single-use indicators tailored to specific cold chain transport
Comments: Minimum order:	advanced indicator enables logi if and when cold chain breaks o (LCD) combines complete alarm maximum or minimum temperat The indicators are factory config vaccine procurement and transp monitor up to three time-temper monitoring requirements beyond Automatic generation of Adobed of alarms: (1) Single event alarm time period, (2) Cumulative time total sum of time. User-friendly accept/reject decision making a records elapsed time at point of	istics staff, receivers and quecur in the supply chain. The n status information with an ture. gured with WHO established port requirements. These contrature alarms, which can be d WHO/UNICEF vaccine show the vaccine shows are triggered if temperature event alarms are triggered three button interface and in nd detailed excursion histor	ality assurance personnel to determine e user-friendly liquid crystal display alarm time-stamp record and the d alarm profiles in support of UNICEF st-effective, single-use indicators tailored to specific cold chain transport ipments. Its main features are: rt; Integrated USB connector; Two types ure exceeds threshold for a contiguous if temperature exceeds threshold for a ntuitive display enables immediate y information. Alarm "time stamp"
	advanced indicator enables logi if and when cold chain breaks o (LCD) combines complete alarm maximum or minimum temperat The indicators are factory config vaccine procurement and transp monitor up to three time-temper monitoring requirements beyond Automatic generation of Adobed of alarms: (1) Single event alarm time period, (2) Cumulative time total sum of time. User-friendly accept/reject decision making a records elapsed time at point of and institute corrective actions.	istics staff, receivers and quecur in the supply chain. The n status information with an ture. gured with WHO established port requirements. These co- rature alarms, which can be d WHO/UNICEF vaccine sh PDF cold chain data repoints are triggered if temperature event alarms are triggered three button interface and in nd detailed excursion histor alarm events, allowing supp	ality assurance personnel to determine e user-friendly liquid crystal display alarm time-stamp record and the d alarm profiles in support of UNICEF st-effective, single-use indicators tailored to specific cold chain transport ipments. Its main features are: rt; Integrated USB connector; Two types ure exceeds threshold for a contiguous if temperature exceeds threshold for a ntuitive display enables immediate y information. Alarm "time stamp" ply chain partners to analyze variability
Minimum order:	advanced indicator enables logi if and when cold chain breaks of (LCD) combines complete alarm maximum or minimum temperat The indicators are factory config vaccine procurement and transp monitor up to three time-temper monitoring requirements beyond Automatic generation of Adobed of alarms: (1) Single event alarm time period, (2) Cumulative time total sum of time. User-friendly accept/reject decision making a records elapsed time at point of and institute corrective actions.	istics staff, receivers and quecur in the supply chain. The n status information with an ture. gured with WHO established boot requirements. These contrequirements. These contreature alarms, which can be distributed who/UNICEF vaccine ships are triggered if temperate event alarms are triggered three button interface and in the detailed excursion histor alarm events, allowing suppressional states and the states and	ality assurance personnel to determine e user-friendly liquid crystal display alarm time-stamp record and the d alarm profiles in support of UNICEF st-effective, single-use indicators tailored to specific cold chain transport ipments. Its main features are: rt; Integrated USB connector; Two types ure exceeds threshold for a contiguous if temperature exceeds threshold for a ntuitive display enables immediate y information. Alarm "time stamp" ply chain partners to analyze variability 2014
Minimum order: Quality standard:	advanced indicator enables logi if and when cold chain breaks o (LCD) combines complete alarm maximum or minimum temperat The indicators are factory config vaccine procurement and transp monitor up to three time-temper monitoring requirements beyond Automatic generation of Adobed of alarms: (1) Single event alarm time period, (2) Cumulative time total sum of time. User-friendly accept/reject decision making a records elapsed time at point of and institute corrective actions. 20 - ISO 9001:2008 -	istics staff, receivers and quecur in the supply chain. The n status information with an ture. gured with WHO established over requirements. These contrature alarms, which can be d WHO/UNICEF vaccine shows are triggered if temperature event alarms are triggered if temperature event alarms are triggered three button interface and in a detailed excursion histor alarm events, allowing support and the price: Year base price: Pieces per carton:	ality assurance personnel to determine e user-friendly liquid crystal display alarm time-stamp record and the d alarm profiles in support of UNICEF st-effective, single-use indicators tailored to specific cold chain transport ipments. Its main features are: rt; Integrated USB connector; Two types ure exceeds threshold for a contiguous if temperature exceeds threshold for a ntuitive display enables immediate y information. Alarm "time stamp" ply chain partners to analyze variability 2014
Minimum order: Quality standard:	advanced indicator enables logi if and when cold chain breaks o (LCD) combines complete alarm maximum or minimum temperat The indicators are factory config vaccine procurement and transp monitor up to three time-temper monitoring requirements beyond Automatic generation of Adobed of alarms: (1) Single event alarm time period, (2) Cumulative time total sum of time. User-friendly accept/reject decision making a records elapsed time at point of and institute corrective actions. 20 - ISO 9001:2008 -	istics staff, receivers and quecur in the supply chain. The n status information with an ture. gured with WHO established bort requirements. These concature alarms, which can be d WHO/UNICEF vaccine sh ® PDF cold chain data repoints are triggered if temperature event alarms are triggered if the button interface and in a detailed excursion histor alarm events, allowing support and vertices per carton: Pieces per carton:	ality assurance personnel to determine e user-friendly liquid crystal display alarm time-stamp record and the d alarm profiles in support of UNICEF st-effective, single-use indicators tailored to specific cold chain transport ipments. Its main features are: rt; Integrated USB connector; Two types ure exceeds threshold for a contiguous if temperature exceeds threshold for a ntuitive display enables immediate y information. Alarm "time stamp" ply chain partners to analyze variability 2014 20
Minimum order: Quality standard:	advanced indicator enables logi if and when cold chain breaks o (LCD) combines complete alarm maximum or minimum temperat The indicators are factory config vaccine procurement and transp monitor up to three time-temper monitoring requirements beyond Automatic generation of Adobed of alarms: (1) Single event alarm time period, (2) Cumulative time total sum of time. User-friendly accept/reject decision making a records elapsed time at point of and institute corrective actions. 20 - ISO 9001:2008 -	istics staff, receivers and quecur in the supply chain. The status information with an ture. gured with WHO established bort requirements. These contractive alarms, which can be di WHO/UNICEF vaccine shills PDF cold chain data reports are triggered if temperate event alarms are triggered three button interface and in and detailed excursion histor alarm events, allowing support alarms per carton: Year base price: Pieces per carton: Weight per carton:	ality assurance personnel to determine e user-friendly liquid crystal display alarm time-stamp record and the d alarm profiles in support of UNICEF ist-effective, single-use indicators tailored to specific cold chain transport ipments. Its main features are: rt; Integrated USB connector; Two types ure exceeds threshold for a contiguous if temperature exceeds threshold for a ntuitive display enables immediate y information. Alarm "time stamp" oby chain partners to analyze variability 2014 20 1.04

Note: If Current PQS status is 'Suspended' or 'Withdrawn', this product is NOT to be purchased.