

WHO Immunisation Devices - Performance, Quality & Safety

E006: Temperature monitoring devices



Product name: LIBERO CS
IMD-PQS Code: E006-023
Status: Prequalified
Date of acceptance: 07 Nov 2013

Appliance type: E006

Product description: User programmable temperature data logger CS

Manufacturer: ELPRO-BUCHS AG

Manufacturers Reference: LIBERO CS
Country of Manufacture: Switzerland

Address: Langaulistrasse 45 9470 Buchs Suisse

Switzerland

366.00

11.00

Telephone: +41 81 552 08 08

Email: andrea.bischof@elpro.com

Website address: http://www.elpro.com/

Valid until: 31 May 2026

Specifications

PRODUCT SPECIFICATIONS - MAIN

Mode of operation Electronic Minimum logging intervals 1.00 (mins)

Maximum logging intervals 60.00 Maximum recording time

(mins) (days)

Sensor type(s) NTC Maximum sensor lead length 0.00

Maximum number of sensor 1.00 External dimensions height

channels (mm)

(II

External dimensions length 96.00 External dimensions width 37.00

(mm)

Activation mechanismStart / stop buttonMaterialABSFixing mechanismNoneCE markingYesMinimum working-30.00Maximum working70.00

temperature (°C) temperature (°C)

MECHANICAL AND ELECTRONIC DEVICES ONLY

Accuracy (+/- °C)0.30Power sourceNon-replaceable batteryBattery typeCR LithiumBattery shelf life (year)min 1 year (no activation)

Activated battery life 1 year Alarm type Visual

Memory capacity (readings) 24200.00 Programmability User Programed

User interfaceUSB for computerDisplay mediumLCDRecording mediumElectronicIngress protection rating IPIP 54

Comments

Accessories: * freeware - liberoCONFIG - Configuration Software* - LIBERO SmartStart - Quick Configuration Tool* - liberoMANAGER - Online Cold Chain Database - elproVIEWER - Analysis Software* - elproASSISTANT - Task Manager The LIBERO CS PDF Logger is a single use data logger with multiple alarm levels that automatically generates an evaluation report in PDF format upon connection to a USB port. No equipment and no software required to read out logger. Release products based on the OK or ALARM status on the display, retrieve the PDF report and forward it to the sender for further analysis or archive it locally. Key features: - up to 8 temperature alarm levels with single or cumulative delays; Alarm on Mean Kinetic Temperature (MKT); Alarm on duration / logging time; Customizable text area for additional information (e.g. shipment information, instructions for recipient, etc.); Chart visualizing the temperature curve and alarm limits

PRICE AND SHIPPING

Shipping volume (m3) 0.003 Weight per Package (Kg) 0.0380 Units per package 40.00 Weight per Unit (Kg) 1.6700

Minimum order	40.00	Incoterms	EXW
Price 1	40+ = 31.06 USD; 120+ = 30.02 USD	Price 2	600+ = 28.44 USD
Price 3	1000+ = on request to manufacturer	Year of base price	2023
QUALITY STANDARD			
Quality Standard	ISO 17025;Other	Quality standard (Other)	ISO 9001:2015
Specification Reference	Applicable PQS specification: E006/TR05.1 Applicable PQS VP(s): E006/TR05-vp.1		
VERIFICATION			
Verification Laboratory	METAS	Address	Lindenweg 50 CH-3003 Bern- WabernSwitzerland
Email	anton.steiner@metas.ch	Verification Report Reference	SAS SCS 122
PRODUCT SITES			
Organization name	ELPRO-BUCHS AG		
Address	Langaulistrasse 45 9470 Buchs Suisse Switzerland		
Current PQS status:	Prequalified	Valid until:	31 May 2026

Note: If Current PQS status is 'Suspended' or 'Withdrawn', this product is NOT to be purchased.