

WHO Immunisation Devices - Performance, Quality & Safety

E006: Temperature monitoring devices



USRID-16WC and USRID-16WA/B Product name:

IMD-PQS Code: F006-070 Status: Prequalified 10 Jan 2020 Date of acceptance:

E006 Appliance type:

Product description: 40 day Electronic Shipping Indicator

LogTag North America Inc. Manufacturer:

Manufacturers Reference: USRID-16WC and USRID-16WA/B

Country of Manufacture: Vietnam

Address: Unit 10, 10 Millpond Drive

> Lafayette New Jersey

United States of America

+64 9 448 2311 Telephone:

Email: quality@logtagrecorders.com Website address: www.logtagrecorders.com

Valid until: 31 May 2025

Specifications

PRODUCT SPECIFICATIONS - MAIN

Electronic Mode of operation Minimum logging intervals 5.00

(mins)

Maximum logging intervals 5.00 Maximum recording time 40.00 (mins)

(days)

Thermistor Maximum sensor lead length Sensor type(s) (metres)

External dimensions height

(mm)

Material

Maximum number of sensor channels

1.00 93.00

External dimensions width

54.50

External dimensions length

(mm)

button

(mm)

Polycarbonate with Lexan label

Activation mechanism Fixing mechanism Minimum working

temperature (°C)

Adhesive -30.00

CE marking Maximum working

temperature (°C)

Yes 70.00

0.00

8.60

MECHANICAL AND ELECTRONIC DEVICES ONLY

Power source Non-replaceable battery **Battery type** 3V LiMnO2 Button cell

Battery shelf life (year) 18 Months **Activated battery life** 7 months Memory capacity (readings) Alarm type Visual 5760.00 Factory Programmed **Programmability** User interface LCD screen LCD Display medium Recording medium **Flectronic**

Ingress protection rating IP IP64

Comments

"The LogTag USRID-16W is an irreversible electronic temperature indicator and recorder for use in monitoring temperature in pharmaceutical transport applications of up to 40 days duration. Each model is factory pre-configured for a range of standard vaccines and provides a clear indication of the shipment's temperature alarm status at all times via the built-in display. The indicator can be started and stopped via push button, and alarms can be reviewed once the trip has been completed. A configurable PDF report with a trip and alarm summary, a chart and a data listing is available when plugged into any PC with a USB port and PDF reader software. Data can also be downloaded to LogTag Analyzer software for detailed analysis if required." Accuracy: Better than ±0.5 °C for -20 °C to +40 °C, better than ±0.7 °C outside this range

PRICE AND SHIPPING

Shipping volume (m3) 0.006 Weight per Package (Kg) 0.0390 Units per package 50.00 Weight per Unit (Kg) 2.3000

Minimum order	20.00	Incoterms	FOB
Price 1	\$27.50 US for 20 - 99 pieces	Year of base price	2020
QUALITY STANDARD			
Quality Standard	Other	Quality standard (Other)	ISO 9001:2015
Specification Reference	Applicable PQS specification: PQS/E006/TR07.3 Applicable PQS VP(s):		
VERIFICATION			
Verification Laboratory		0013X00004MI8OeQAJ	
PRODUCT SITES			
Organization name	LogTag North America Inc.		
Address	Unit 10, 10 Millpond Drive Lafayette New Jersey United States of America		
Current PQS status:	Prequalified	Valid until:	31 May 2025

Note: If Current PQS status is 'Suspended' or 'Withdrawn', this product is NOT to be purchased.