

WHO Immunisation Devices - Performance, Quality & Safety

E006: Temperature monitoring devices



Product name: UTRID-16
IMD-PQS Code: E006-076
Status: Prequalified
Date of acceptance: 18 Mar 2021

Appliance type: E006

Product description: User programmable data logger
Manufacturer: LogTag North America Inc.

Manufacturers Reference: UTRID-16
Country of Manufacture: Vietnam

Address: TongFuYu Industrial Zone, Block NO.8, Jinghong Road,

Shajing Town, Baoan 518117 ShenZhen, GuangDong

China

Telephone: +64 9 448 2311

Email: sales@logtagrecorders.com

Website address: www.logtagrecorders.com

Valid until: 31 May 2025

Specifications

channels

(mm)

PRODUCT SPECIFICATIONS - MAIN

Mode of operationElectronicMinimum logging intervals1.00

(mins)

Maximum logging intervals 1080.00 Sensor type(s) Electronic Thermistor (mins)

Maximum number of sensor 1.00 External dimensions height 8.60

(mm)

External dimensions length 93.00 External dimensions width 54.50

(mm)

Activation mechanism Start button, or start at Material Polycarbonate

configured date and time

Fixing mechanismScrewsCE markingYesMinimum working-30.00Maximum working65.00

Minimum working -30.00 Maximum working temperature (°C) temperature (°C)

MECHANICAL AND ELECTRONIC DEVICES ONLY

Power source Non-replaceable battery Battery type CR2450 3V Li-MnO2 UN38.3

approved coin cell

Battery shelf life (year)12 monthsActivated battery life24 monthsAlarm typeVisualMemory size (Mb)4.0000000000

Memory capacity (readings)16129.00User interfaceUSB / Display / ButtonsDisplay mediumLCD DisplayRecording mediumEEPROM, non-volatile

Ingress protection rating IP IP65

Comments LogTag's UTRID-16 is a fully configurable, multi-use USB PDF temperature recorder with a built-in

display, that can create temperature reports without the need to install proprietary software or hardware at the destination. Select statistical data can be reviewed directly on the display without the need for a PC. The recorder can be configured using LogTag® Analyzer, and is then placed with the goods to be monitored. At the end of the trip, the UTRID-16 can be plugged straight into a computer's USB port and generates a PDF file, which can be accessed using PDF software such as Acrobat Reader. Accuracy: Better than ±0.5 °C for -20 °C to +40 °C, better than ±0.7 °C for -30 °C

to -20 °C and +40 °C to +60

PRICE AND SHIPPING

Shipping volume (m3)0.028Weight per Package (Kg)0.0390Units per package50.00Weight per Unit (Kg)2.3000Minimum order20.00IncotermsEXW

Price 1	48 USD	Year of base price	2021
QUALITY STANDARD			
Quality Standard Specification Reference	Other Applicable PQS specification: Applicable PQS VP(s):	Quality standard (Other)	ISO 9001:2015
VERIFICATION			
Verification Laboratory	TUV SUD PSB Pte Ltd	Address	15 International Business Park TÜV SÜD @ IBP Singapore 609937Singapore
Telephone	+6569736355	Email	xin-pei.kee@tuvsud.com
PRODUCT SITES			
Organization name	LogTag North America Inc.		
Address	TongFuYu Industrial Zone, Block NO.8, Jinghong Road, Shajing Town, Baoan 518117 ShenZhen, GuangDong China		
Current PQS status:	Prequalified	Valid until:	31 May 2025

Note: If Current PQS status is 'Suspended' or 'Withdrawn', this product is NOT to be purchased.