



## E007 VS: Cold chain accessories



<b>Product name:</b>	<b>SVS04-22E5 4A 1KVA 110-285V 6MIN EURO</b>
<b>IMD-PQS Code:</b>	E007-013
<b>Status:</b>	Prequalified
<b>Date of acceptance:</b>	27 May 2026
<b>Appliance type:</b>	E007
<b>Product description:</b>	Single-phase Voltage Stabilizer - Extended Range
<b>Manufacturer:</b>	Sollatek (UK) Limited
<b>Manufacturers Reference:</b>	SVS04-22E5 4A 1KVA 110-285V 6MIN EURO
<b>Country of Manufacture:</b>	United Kingdom
<b>Address:</b>	Sollatek House, Waterside Drive, Langley Buckinghamshire United Kingdom of Great Britain and Northern Ireland
<b>Telephone:</b>	+441753214500
<b>Email:</b>	<a href="mailto:maan.allos@sollatek.com">maan.allos@sollatek.com</a>
<b>Website address:</b>	<a href="http://www.sollatek.com">www.sollatek.com</a>
<b>Valid until:</b>	31 May 2027

## Specifications

### PRODUCT SPECIFICATIONS - MAIN

<b>Climate zone</b>	Multizone	<b>Power Input (W)</b>	1000.00
<b>Nominal Power (W)</b>	1000.00		

### PRODUCT SPECIFICATIONS - ADDITIONAL

<b>Nominal Input Frequency (Hz)</b>	50.00	<b>Nominal Input Voltage (V)</b>	230.00
<b>Nominal Output Frequency (Hz)</b>	50.00	<b>Nominal Output Voltage (V)</b>	230.00
<b>Input frequency regulation range (Hz)</b>	50-60	<b>Input Voltage Regulation Range (V)</b>	110-285
<b>Output Current (A)</b>	4.00	<b>Short Circuit Protection Type</b>	yes
<b>Overload Protection Type</b>	yes	<b>Overvoltage Endurance Electrical Withstand (V)</b>	500.00
<b>Impulsive Transient Protection (kA)</b>	6.50	<b>Power Rating (kVA)</b>	1.00
<b>Ingress protection rating IP</b>	31	<b>Maximum Rated Ambient Temp (°C)</b>	55.00
<b>Minimum Rated Ambient Temp (°C)</b>	-10.00	<b>External dimensions height (mm)</b>	131.00
<b>External dimensions length (mm)</b>	277.00	<b>External dimensions width (mm)</b>	161.00
<b>Power Lead Length (m)</b>	1.50	<b>Mode of operation</b>	Electronic
<b>Alarm function(s)</b>	digital display	<b>Control Panel Display</b>	digital LCD
<b>Display medium</b>	LCD	<b>Enclosure Material</b>	plastic
<b>CE marking</b>	Yes	<b>Efficiency Percentage (%)</b>	98.00
<b>Relative Humidity Rating (%)</b>	95.00		

### PRICE AND SHIPPING

<b>Shipping weight (kg)</b>	7.20	<b>Weight per Package (Kg)</b>	15.0000
<b>Weight per Unit (Kg)</b>	7.0	<b>Minimum order</b>	2.00
<b>Units per package</b>	2.00	<b>Price</b>	177
<b>Year of base price</b>	2026	<b>Incoterms</b>	FCA

### QUALITY STANDARD

<b>Quality Standard</b>	Other	<b>Quality standard (Other)</b>	ISO 9001:2015
-------------------------	-------	---------------------------------	---------------

**VERIFICATION**

<b>Verification Laboratory</b>	Labor SA	<b>Address</b>	Ethnikis Antistaseos 84, Pallini, P.C. 15351, GreeceGreece
<b>Telephone</b>	+30 2106033377	<b>Email</b>	labor@labor.gr
<b>Verification Report Reference</b>	0781.042.3.01		

---

**PRODUCT SITES**

<b>Organization name</b>	Sollatek (UK) Limited
<b>Address</b>	Sollatek House, Waterside Drive, Langley Buckinghamshire United Kingdom of Great Britain and Northern Ireland

---

<b>Current PQS status:</b>	<i>Prequalified</i>	<b>Valid until:</b>	<i>31 May 2027</i>
----------------------------	---------------------	---------------------	--------------------

---

Note: If Current PQS status is 'Suspended' or 'Withdrawn', this product is NOT to be purchased.